Rittal - The System.

Faster – better – everywhere.





SK 3178.800 Blue e+ S wall-mounted cooling unit

State: 15/12/2025 (Source: rittal.com/ro-ro)



SK 3178.800 - Blue e+ S wall-mounted cooling unit 0.3 kW - 1 kW

Blue e+ S cooling units with tried-and-tested Blue e+ technology are the world's most energy-efficient cooling units. This means they reduce the carbon footprint of your machines and systems. Available in a brand new design with a host of smart functions.

Features

| Model No. | SK 3178.800 |
|-------------------------|--|
| Design | wall-mounted |
| Benefits | Contributes to climate-neutral production with average energy |
| | savings of 75% and a reduced carbon footprint |
| | Multi-voltage capabilities and country-specific approvals support global usability |
| | Smart, simple monitoring via IoT interface |
| | User-friendly operation with the Rittal Scan & Service app |
| Material | Sheet steel |
| General colour | RAL 7035 |
| Colour | Enclosure: RAL 7035 |
| | Louvred grille: RAL 7012 |
| Supply includes | Assembly parts |
| | Fully wired ready for connection (plug-in terminal strip) |
| | Integral electric condensate evaporation |
| Options | For remote monitoring and networking of cooling units and chillers |
| | in the Blue e+ generation, please use the IoT interface (Model No. |
| | 3124.300). Increase machine availability and process reliability with |
| | remote monitoring of device data, statuses and system messages. |
| Total cooling output to | Cooling output L35 L35/50 Hz: 0.3 kW |
| DIN EN 14511 | Cooling output L35 L35/60 Hz: 0.3 kW |
| | Cooling output L35 L50/50 Hz: 0.22 kW |
| | Cooling output L35 L50/60 Hz: 0.22 kW |
| Rated operating voltage | 110 V - 240 V, 1~, 50 Hz/60 Hz |

© Rittal 2025 2

Features

| Note | Please observe the mounting instructions. By downloading the software, a contract is concluded between the contractual partner and Rittal for the free use of the software in accordance with these licence conditions. Only suitable for use in semi-outdoor areas (see instructions for description) |
|---|--|
| Note on Model No. | Tolerance: 110 V -10% (99 V) and 240 V +10% (264 V) |
| Rated power input | 0,22 kW |
| Air throughput (unimpeded air flow) | External circuit: 366.6 m³/h Internal circuit: 366.6 m³/h |
| Energy efficiency ratio (EER) 50/60 Hz L35 L35 | Refrigeration factor L35 L35 (EER) 50 Hz: 1.8 Refrigeration factor L35 L35 (EER) 60 Hz: 1.8 |
| Design | wall-mounted |
| Dimensions | Width: 300 mm Height: 570 mm Depth: 159 mm |
| Required mounting cut-out | Cut-out width: 280 mm Cut-out height: 550 mm |
| Protection category to IEC 60 529 | Internal circuit IP 55 |
| Protection category NEMA | UL Type 12 UL Type 3R |
| Refrigerant/cooling medium | Refrigerant: R-513A Quantity: 0.13 kg Global Warming Potential (GWP): 631 CO2 equivalent (CO2e): 0.08 t |
| Temperature control | e+ controller (factory setting +35 °C) |
| Operating temperature range | -20 °C60 °C |
| Storage temperature range | -40 °C70 °C |
| Operating temperature range of refrigerant circuit (active) | 3 °C60 °C |
| Heat pipe operating temperature range | -20 °C45 °C |

© Rittal 2025 3

Features

| Setting range | 20 °C50 °C |
|--|---|
| Power consumption Pel | Power consumption L35 L35/50 Hz: 0.17 kW Power consumption L35 L35/60 Hz: 0.17 kW Power consumption L35 L50/50 Hz: 0.2 kW Power consumption L35 L50/60 Hz: 0.2 kW |
| Permissible operating pressure (p. max.) | 32 bar |
| Packs of | 1 pc(s). |
| Net weight | 12.2 |
| Gross weight | 13.2 |
| Customs tariff number | 84158200 |
| EAN | 4028177949959 |
| ETIM 9 | EC000855 |
| ETIM 8 | EC000855 |
| ECLASS 8.0 | 27180704 |

Approvals

| Approvals | 30 - KC Korea |
|--------------|--|
| | UL + C-UL (listed) |
| | UL + C-UL - FTTA |
| Explanations | Declaration of conformity |
| | Declaration of conformity - F-gas regulation |

© Rittal 2025

Tender text

3178800

Wallmounted cooling unit Blue e+ S

Blue e+ S cooling units with proven Blue e+ technology

offer the world's highest energy efficiency.

This is also associated with the reduction of the CO2 footprint of machines and systems.

Benefits:

Contribution to climate-neutral production thanks to average energy savings of 75% and reduction of CO2 footprint.

Increased environmental friendliness through use of refrigerant R-513A. Worldwide usability due to multi-voltage capability and country-specifi approvals.

Intelligent and easy monitoring via IoT interface.

Convenient operation with Rittal Product Scan & Service App.

Total cooling output L35 L35 50/60 Hz: 0,3 kW / 0,3 kW

Total cooling output L35 L50 50/60 Hz: 0,22 kW / 0,22 kW

Power consumption L35 L35 50/60 Hz: 0,17 kW / 0,17 kW

Power consumption L35 L50 50/60 Hz: 0,2 kW / 0,2 kW

Rated power input: 0,22 kW

Rated operating voltage: 110 V - 240 V, 1~, 50 Hz/60 Hz Temperature control: e+ controller (factory setting +35 °C)

Dimensions [WxHxD]: 300 x 570 x 159 mm

Material: Sheet steel

Colour: Housing: RAL 7035 / Louvre grille: RAL 7012

Refrigeration factor L35 L35 (EER) 50 Hz: 1,8

Refrigerant / Quantity:R-513A / 0,13 g

Operating temperature range: -20 °C to 60 °C

Setting range: 20 °C to 50 °C

Storage temperature range: -40 °C to 70 °C

Protection category IP to IEC 60 529: Internal circuit IP 55

Protection category NEMA: UL Type 3R/12

Weight: 12,2 kg

Note: With integrated condensate evaporation

© Rittal 2025 5