

# Rittal – The System.

Faster – better – everywhere.



## DK 5301.561

## Sheet steel door, one-piece, vented

State: 20/07/2025 (Source: [rittal.com/ro-ro](https://www.rittal.com/ro-ro))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 5301.561 - Sheet steel door, one-piece, vented for VX IT

To replace existing doors. The vented surface area is approx. 85% perforated.



## Features

|                      |  |
|----------------------|--|
| Model No.            | DK 5301.561  |
| Product description  | To replace existing doors. The vented surface area is approx. 85% perforated.  |
| Material             | Sheet steel  |
| Surface finish       | Spray-finished   |
| Colour               | Door: RAL 7035<br>Comfort handle VX: RAL 9005  |
| Supply includes      | Door with comfort handle for semi-cylinders with security lock 3524 E<br>3 x 130° hinges, fitted on the inside<br>Assembly parts |
| Assembly instruction | For a door opening angle of 180° when baying, a 180° baying hinge is required  |
| Note                 | Door opening angle for stand-alone siting: max. 165°<br>Door opening angle when baying: max. 110°                                |

# Features

|                               |  |
|-------------------------------|--|
| To fit                        | Enclosure type: VX IT<br>Width: = 600 mm<br>Height: = 2,000 mm   |
| Packs of                      | 1 pc(s).   |
| Net weight                    | 12.2   |
| Gross weight                  | 13.2   |
| PCF per pack (cradle-to-gate) | 50.3 kg CO2 eq (Cat B)   |
| Note on PCF category          | Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared |
| EAN                           | 4028177955103  |
| ETIM 9                        | EC000747   |
| ECLASS 8.0                    | 27182204   |