

**Rittal – The System.**

Faster – better – everywhere.



**DK 7030.490**

**CMC III CAN bus connection cable**

State: 24/08/2025 (Source: [rittal.com/ro-ro](http://rittal.com/ro-ro))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# DK 7030.490 - CMC III CAN bus connection cable

Connects CAN bus units for information and power transmission.

## Features

Model No.	DK 7030.490
Product description	For connecting the PU to the CAN bus sensors III, units III and control units III as a bus, also for cabling together. Because it is available in different lengths, the CMC III system can be adapted to various applications and built to a custom design.
Applications	For connecting the CAN bus units. Information and power transfer of the individual CAN bus units.
Length	4 m
Dimensions	Length: 4 m
Interfaces/connections	Connector (type): RJ45RJ45
Operating temperature range	0 °C...55 °C
Ambient humidity (non-condensing)	5...95 %
Packs of	1 pc(s).
Net weight	0.1
Gross weight	0.16
Customs tariff number	85444290
EAN	4028177695931
ETIM 9	EC000313
ECLASS 8.0	27189253

# Tender text

7030.490

CMC III CAN bus connection cable

Packs of 1

This can be used to connect the PU with the CAN bus sensors, units and control units as a bus. Also for cabling together. The cable is used to transmit information and power to the individual CAN bus units.

Technical specifications:

Connector 1: RJ45

Connector 2: RJ45

Length: 4 m

Temperature application range:

0 °C to 55 °C

Humidity range:

5% to 95% relative humidity, non-condensing

Included in the pack: Cable and cable holder