

Rittal – The System.

Faster – better – everywhere.



DK 7111.212

Cable routing bars for universal use

State: 21/06/2026 (Source: rittal.com/ro-ro)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7111.212 - Cable routing bars for universal use

For structured routing of entire cable bundles, all-round attachment for universal use, connection comb.

Features

| | |
|-------------------------------|---|
| Model No. | DK 7111.212 |
| Product description | For structured routing of entire cable bundles, the cable bars may be secured to a variety of different positions inside the enclosure. |
| Applications | All-round attachment for universal use for vertical and horizontal cable routing inside the enclosure or within the distributor level. |
| Material | Support: Sheet steel Cable routing bars, connection combs: Plastic UL 94-V0 |
| Colour | RAL 9005 |
| Supply includes | Cable routing bars Connection combs |
| Number connection combs | 5 |
| Note | Size of individual chambers (WxD) approx. 34 x 100 mm |
| Units | 1 U |
| Packs of | 10 pc(s). |
| Net weight | 0,74 kg |
| Gross weight | 0,845 kg |
| PCF per pack (cradle-to-gate) | 3.2 kg CO2 eq (Cat B) |
| Note on PCF category | Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared |
| Customs tariff number | 73269098 |
| ETIM 9 | EC000322 |
| ECLASS 8.0 | 27400604 |
| Product description | DK Cable routing bars for universal use, 1 U, RAL 9005 |

Tender text

Cable bracket, 1U

1 U single cable bracket for guiding cables horizontally and vertically in the enclosure or within the distribution level or for extending existing units by baying by means of connecting piece. For this the connecting piece is put between two bracket elements and thus connects the elements by forming an additional guide chamber between the bracket elements. The connecting pieces needed for baying are contained within the units. delivery scope. The single bracket has a height of approx one height unit (44.45 mm) and thus enables the U related cable feed of whole cable bunches.

Each individual cable bracket can be opened selectively and independently of the others and closed again by means of a turning catch. It thus enables straightforward structuring of the cabling and also flexible change to it

Support element sheet steel, spray finished

Cable feed brackets, connecting pieces, turning catches, plastic