

# Rittal – The System.

Faster – better – everywhere.



## DK 7320.721 Handles, electromagnetic

State: 22/05/2026 (Source: [rittal.com/ro-ro](http://rittal.com/ro-ro))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

# DK 7320.721 - Handles, electromagnetic for CMC III and IoT Interface

Handles may be integrated into various enclosure systems.

## Features

|  |   |
|--|---|
| Model No.                                    | DK 7320.721   |
| Design                                       | Comfort handle:with master key function   |
| Product description                          | For control and monitoring via a central CMC III type control unit and IoT interface.   |
| Colour                                       | RAL 7035  |
| Supply includes                              | 2 adaptors for glazed door<br>Cable clamps<br>Adaptor for profile half-cylinders<br>Connection cable (3 m) with RJ 12 connector<br>Assembly parts |
| Lock type                                    | Master key function (with emergency open function)  |
| Rated current max.                           | 0,1 A   |
| No. of participants per IoT interface (max.) | 16  |
| No. of participating PU compact (max.)       | 2   |
| No. of participating PU (max.)               | 16  |
| Number subscribers per PDU note              | Max. 5 p. for power supply with PoE   |
| Packs of                                     | 1 pc(s).  |
| Net weight                                   | 0,99 kg   |
| Gross weight                                 | 0,992 kg  |
| Customs tariff number                        | 83024110  |
| ETIM 9                                       | EC000327  |
| ECLASS 8.0                                   | 27409217  |

# Features

---

|                     |  |
|---------------------|--|
| Product description | DK CMC III Comfort handle, with Master key function, For TS 8, DK-TS |
|---------------------|--|

# Approvals

---

|              |   |
|--------------|---|
| Explanations | Manufacturer's declaration<br>Declaration of conformity |
|--------------|---|

# Tender text

Comfort handle for TS 8 with master-key function,,,,,,,,,,,,,  
The TS 8 handle includes the master key function.  
This means that, independently of the control system,  
the handle can always be opened using the master-key.  
The door can be released via the CMC-TC system.  
In addition an access unit (V1.1) and an access sensor  
(7320.530) should be used so that the door status can  
be polled.

Technical specifications:

- Rated voltage: 24 V DC
- Rated current: max. 100 mA
- Connection cable: Length 3 m, RJ 12 connector
- Connection cable: Length 2 m, RJ 12/RJ 12 connector
- Extension coupling: RJ 12/RJ 12 jack
- Temperature application range: +5°C to +40°C
- Protection category: IP 40