

# Rittal – The System.

Faster – better – everywhere.



## RX 9360.101

## RiLineX end module set

State: 06/07/2026 (Source: [rittal.com/ro-ro](http://rittal.com/ro-ro))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# RX 9360.101 - RiLineX end module set for basic module

RiLineX end module set, 3-pole, for the modular RiLineX board. This set forms board ends on the left and right, including all-round contact hazard protection. One of these is required for each modularly assembled RiLineX board system.



## Features

|                  |  |
|------------------|--|
| Model No.        | RX 9360.101  |
| Benefits         | Scalable system lengths with basic modules<br>Simple assembly<br>Scalable rated currents thanks to variable busbar cross-sections<br>Tested short-circuit resistance up to 65 kA<br>Suitable for applications up to 1000 V AC and up to 1500 V DC<br>Extensive range of system accessories<br>Contact hazard protection up to IP 2XB, upgradable to IP 3X<br>Tested and certified to IEC and UL<br>Simple extension and baying |
| Material         | Polyamide (PA 6)<br>Fire protection corresponding to UL 94   |
| Colour           | RAL 35745  |
| Supply includes  | Board end element, left<br>Board end element, right<br>Assembly parts  |
| To fit Model No. | 9360110<br>9360120<br>9360150  |

# Features

|                               |   |
|-------------------------------|---|
| Number of poles               | 3-pole  |
| Dimensions                    | Width: 105 mm<br>Height: 240 mm<br>Depth: 49.2 mm   |
| Packs of                      | 2 pc(s).  |
| Net weight                    | 1 kg  |
| Gross weight                  | 1,151 kg  |
| PCF per pack (cradle-to-gate) | 6.65  |
| Customs tariff number         | 85472000  |
| ETIM 9                        | EC002270  |
| Product description           | RiLineX end module set for the 3-pole modular RiLineX board. This set forms board ends on the left and right, including all-round contact hazard protection. One of these is required for each modularly assembled RiLineX board system. The supply includes one left-hand end module and one right-hand end module, plus assembly parts. |

# Approvals

|              |  |
|--------------|--|
| Approvals    | UL + C-UL (listed)                           |
| Explanations | Declaration of conformity<br>PCF-declaration |

# Tender text

## RiLineX Endmodul-Set für Basismodul

RiLineX end module set, for the modular RiLineX board.  
This set forms board ends on the left and right,  
including all-round contact hazard protection.  
One of these is required for each modularly

assembled RiLineX board system.

For voltages up to 1000 V AC and 1500 V DC.

Tested short-circuit resistance up to 65 kA.

IEC and UL approved.

Product information

Number of poles: 3

Busbar dimensions: 15/20/30 mm x 5/10 mm

Rated current max.: 550/800 A

Dimensions: 105 mm x 246 mm x 49,2 mm (WxHxD)

Manufacturer: Rittal GmbH & Co. KG

Type: 9360101