



SV 9661.230 - PE/PEN combination angle E-Cu for PE/ PEN combinations

The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.

Features

Model No.	SV 9661.230
Product description	The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.
Benefits	Thanks to the pre-assembled combination angles, baying brackets and busbars customised to match the enclosure width, assembly is time-saving with cost reduction
Applications	Form 2-4 Other
Material	E-Cu
Supply includes	Assembly parts
Approved short-circuit current capability	I _{cw} 30 kA, 1 sec.
To fit busbars	Busbar E-Cu with integral punchings
OUT_CROSS_SECTION_COL_SM	30 - 10 mm
To fit busbars	Width: 30 Height: 10 mm
Packs of	4 pc(s).
Net weight	2 kg
Gross weight	2,177 kg
Copper weight (kg per piece)	0,408
Customs tariff number	74198090
ETIM 9	EC000329

Features

ECLASS 8.0

27400605

Product description

SV PE/PEN combination angle E-Cu, WH: 30x10 mm

Approvals

Explanations

Declaration of conformity

Declaration of conformity UK