


Rittal – The System.

Faster – better – everywhere.



VX 9680.025

Bayed enclosure system VX25

State: 09/01/2026 (Source: rittal.com/ro-ro)



FRIEDHELM LOH GROUP

VX 9680.025 - Bayed enclosure system VX25 Fuse-switch-disconnector enclosure

Baying systems for the distribution of electrical power with NH slimline fuse-switch disconnectors (ABB or Jean Müller).



Features

| | |
|-----------------------------------|---|
| Model No. | VX 9680.025 |
| Material | Sheet steel, 1.5 mm |
| Surface finish | Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Gland plates: Zinc-plated |
| Colour | RAL 7035 |
| Supply includes | Enclosure frame Door Roof plate Rear panel Gland plates Front trim panels Lock: 3 mm double-bit Compartment side panels Locating frame for disconnectors with fuses (brands ABB SlimLine/ Jean Müller SASIL) |
| Protection category to IEC 60 529 | Up to IP 2X (depending on the panels) |

Features

| | |
|-------------------------------|--|
| Test specification | IEC 61 439-1/-2 IEC 61 641 |
| Dimensions | Width: 1,000 mm Height: 2,200 mm Depth: 600 mm |
| Packs of | 1 pc(s). |
| Net weight | 135.2 |
| Gross weight | 146.4 |
| PCF per pack (cradle-to-gate) | 333.1 kg CO2 eq (Cat B) |
| Note on PCF category | Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared |
| EAN | 4028177937048 |
| ETIM 9 | EC000261 |
| ECLASS 8.0 | 27180101 |

Approvals

| | |
|--------------|---|
| Certificates | Surface finish |
| Explanations | Declaration of conformity Declaration of conformity UK |