

Rittal – The System.

Faster – better – everywhere.



SV 9320 030 Busbar connector

State: 12/05 2016 (Source: rittal.com/r3-sr)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9320.030 - Busbar connector

For connecting busbars, no drilling required.

Features

Model No.	SV 9320.030
Product description	For connecting rectangular busbars, no drilling required.
Material	Top piece: Sheet steel, zinc-plated, passivated Contact plate: E-Cu, silver-plated
Connection type	Baying connection from enclosure to enclosure
To fit busbars	20 x 5 - 30 x 10
Packs of	3 pc(s).
Net weight	1,881 kg
Gross weight	2,02 kg
Copper weight (kg per piece)	0,35
PCF per pack (cradle-to-gate)	7.9 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	85369010
ETIM 9	EC000713
ECLASS 8.0	27400606
Product description	SV Busbar connector, for E-Cu 20x5-30x10 mm, bayed connection

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK

Tender text

Busbar connector

Baying connectors for connecting rectangular busbars, no drilling required.

Design

Baying connection from enclosure to enclosure for busbars 20 x 5 - 30 x 10

System:

Rittal RiLine60