

Rittal – The System.

Faster – better – everywhere.



SG 2368.000

Connection component

State: 12/08/2025 (Source: rittal.com/sg-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SG 2368.000 - Connection component for signal pillar, modular

Optionally for conduit or wall/base mounting, with cover for optical components.

Features

| | |
|---|---|
| Model No. | SG 2368.000 |
| Design | for conduit mounting |
| Product description | Optionally for conduit or wall/base mounting. Screw terminals in the connection component. With cover for optical components. Contact hazard protection to VDE. |
| Benefits | Simple assembly and contact via bayonet fastener. |
| Function principle | A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel |
| Material | Enclosure of polyamide |
| Colour | Black |
| Diameter | 70 mm |
| Rated impulse withstand voltage, phase to phase | 2500 V AC |
| Rated insulation voltage | 250 V AC |
| Signal pillar | modular |
| Dimensions | Height: 43 mm |
| Protection category to IEC 60 529 | IP 54 |
| Rated operating voltage | 12 V - 240 V (AC/DC) |
| Packs of | 1 pc(s). |
| Net weight | 0.11 |
| Gross weight | 0.115 |
| Customs tariff number | 85369095 |
| EAN | 4028177219908 |

Features

| | |
|------------|----------|
| ECLASS 8.0 | 27371232 |
|------------|----------|

Approvals

| | |
|-----------|--------------------------|
| Approvals | UL + C-UL (listed) UR |
|-----------|--------------------------|