Rittal – The System.

Faster – better – everywhere.





SZ 2482.300

Mounting frame, interface flap, modular

State: 15/08/2025 (Source: rittal.com/sg-en)



SZ 2482.300 - Mounting frame, interface flap, modular

Suitable for universal use, for rapid access to interfaces and sockets, the affected enclosure remains closed.

Features

Model No.	SZ 2482.300		
Design	Mounting frame, single, with plastic flap (semi-transparent)		
Product description	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed an is therefore protected from ambient influences and unauthorised access.		
Function principle	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required.		
Material	Lock: Polycarbonate Mounting frame, refined die-cast zinc Plastic flap: Polycarbonate (semi-transparent)		
Surface finish	Mounting frame: Matt nickel-plated		
Colour	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)		
Mounting cut-out	Cut-out width: 52 mm Cut-out height: 91 mm		
Installation options	In small and compact enclosures as a programming interface for controllers In IT and industrial distributors as maintenance access for networks In PC enclosures and console systems for the temporary connection of additional equipment in mobile Industrial Workstations for rapid connection to existing network structures In command panel systems for programming and maintenance of integral components.		

© Rittal 2025

Features

Dimensions	Width: 65 mm Height: 120 mm	
IP protection category to IEC 60 529	IP 65 with sealed flap and proper assembly	
Packs of	1 pc(s).	
Net weight	0.199	
Gross weight	0.208	
Customs tariff number	85369095	
EAN	4028177311695	
ETIM 9	EC002625	
ETIM 8	EC002625	
ECLASS 8.0	27189234	

Approvals

Explanations	Declaration of conformity	
--------------	---------------------------	--

© Rittal 2025 3