Rittal – The System.

Faster - better - everywhere.



SK 3286.970 Air duct system

State: 30/06/2025 (Source: rittal.com/sg-en)



POWER DISTRIBUTION X CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3286.970 - Air duct system for roof-mounted cooling units and roof-mounted air-water heat exchangers

The air duct system allows cold air to be routed directly to specific areas of the enclosure. This effectively eliminates the risk of air short-circuits due to self-ventilated installed devices. The shallow ducts can be cut to the desired length.

Features

| Model No. | SK 3286.970 | |
|-----------------------|---|--|
| Product description | Cold air may be routed directly to specific areas of the enclosure using the air duct system. The risk of air short circuits due to self- ventilated installed devices is therefore eliminated. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length. | |
| Material | Flame-resistant plastic to DIN 4102/B1 | |
| Colour | RAL 7035 | |
| Supply includes | Shallow duct Compensating hose (length approx. 1 m) | |
| Note | Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unit may be reduced, depending on the application in question. For devices 3359/3382, the air duct adaptor 3286.840 is additionally required. | |
| To fit Model No. | 3386 3387 | |
| Packs of | 1 pc(s). | |
| Net weight | 2.9 | |
| Gross weight | 3 | |
| Customs tariff number | 39269097 | |
| EAN | 4028177325456 | |
| ETIM 9 | EC011444 | |
| | | |

Features

| ETIM 8 | EC011444 | |
|------------|----------|--|
| ECLASS 8.0 | 22410601 | |
| | | |
| | | |
| Approvals | | |

Certificates

EAC