

# Rittal – The System.

Faster – better – everywhere.



## SK 3301.950

## Cooling medium (ready-mixed)

State: 13/05/2026 (Source: [rittal.com/sg-en](http://rittal.com/sg-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3301.950 - Cooling medium (ready-mixed) For chillers and air-water heat exchangers

As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection.

## Features

Model No.	SK 3301.950
Product description	As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection.
Contents	10 l
Antifreeze/water mixture	1 : 2
Delivery form	Canister
Rifrost	Outdoor
Operating temperature range	-20 °C...60 °C
Packs of	1 pc(s).
Net weight	10 kg
Gross weight	10.8 kg
Customs tariff number	38200000
ETIM 9	EC001243
ETIM 8	EC001243
ECLASS 8.0	23061202
Product description	SK Cooling medium for chillers, glycol/water mixture : 1:2, container: 10 l, Outdoor

# Tender text

Rifrost-Outdoor 10 l for water circuits

Apart from the recooling systems for oil and emulsion, all other recooling systems are only suitable for the cooling of water or a water/glycol mixture.

As well as protecting against frost, these also serve to impair bacterial growth and achieve optimum corrosion protection.

Technical data

RiFrost: Outdoor

Glycol/water mixture: 1:2

Container: 10 l

(Safety data sheets under Downloads)