

Rittal – The System.

Faster – better – everywhere.



TS 4594.000 Support strip

State: 10/09/2025 (Source: [rittal.com/sg-en](https://www.rittal.com/sg-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 4594.000 - Support strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



Features

| | |
|---|--|
| Model No. | TS 4594.000 |
| Product description | For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment. |
| Technical specifications | 4.5 mm diameter hole on a 25 mm pitch pattern |
| Material | Sheet steel |
| Surface finish | Zinc-plated |
| Supply includes | Assembly parts |
| Length | 290 mm |
| To fit door width | 400 mm |
| VX SE installation options | In door width 400 mm |
| AX installation options | In enclosure width 300 mm and in enclosure height 400 mm, in conjunction with rail for interior installation AX |
| AX stainless steel installation options | In enclosure width 300 mm |
| Installation options, AX plastic | In door width 400 mm |
| Installation options for 3-part AX | In enclosure depth 473 mm |
| TS installation options | In door width 400 mm |

Features

| | |
|--|---|
| Installation options for VX base/ plinth, stainless steel | In base/plinth depth 400 mm, in conjunction with M6 multi-tooth screws and M6 nuts |
| To fit | Enclosure type: VX TS VX SE AX AX plastic AX wall-mounted enclosure, 3-part |
| To fit | VX base/plinth system, stainless steel |
| Packs of | 20 pc(s). |
| Net weight | 2.94 |
| Gross weight | 3.02 |
| PCF per pack (cradle-to-gate) | 11.4 kg CO2 eq (Cat B) |
| Note on PCF category | Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared |
| Customs tariff number | 73269098 |
| EAN | 4028177103726 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |