

Rittal – The System.

Faster – better – everywhere.



DK 7111.900

Cable shunting ring

State: 27/01/2026 (Source: rittal.com/sg-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7111.900 - Cable shunting ring

For flexible, system-compatible cable routing at the side of the 482.6 mm (19") mounting angles.



Features

Model No.	DK 7111.900
Product description	For flexible, system-compatible cable routing at the side of the 482.6 mm (19") mounting angles.
Material	Steel
Surface finish	Zinc-plated
Supply includes	Assembly parts
Dimensions	Height: 85 mm Depth: 125 mm
Packs of	10 pc(s).
Net weight	0.95
Gross weight	0.991
PCF per pack (cradle-to-gate)	5.3 kg CO ₂ eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	83024200
EAN	4028177147928
E-Number Sweden	E7239799
ETIM 9	EC000322

Features

ECLASS 8.0

27400604

Tender text

Cable shunting ring, zinc-plated, passivated

The zinc-plated, passivated cable shunting rings, made from HxD 85 x 125 mm steel sheet, are fitted on telecommunication system strips or direct in telecommunication distribution enclosures and support the flexible, system-compatible cable routing.

Material: Sheet steel, zinc-plated, passivated

Dimensions: HxD 85 x 125 mm

Packs of 10