
### Rittal – The System.

Faster – better – everywhere.





### VX 8100.743


# Punched section without mounting flange, 23 x 64 mm

State: 14/12/2025 (Source: rittal.com/sg-en)



## VX 8100.743 - Punched section without mounting flange, 23 x 64 mm for VX, VX SE

For variable, individual interior installation of the enclosure frame on the inner mounting level.



#### **Features**

Model No.	VX 8100.743
Product description	For variable, individual interior installation of the enclosure frame or the inner mounting level. Mounted flush with enclosure frame The additional mounting brackets mean it can also be used with a pre- installed mounting plate, and is also prepared for cutting to any required length.
Benefits	System punchings on all four sides With slots at the top and bottom for cage nuts, for attaching your own components via metric screws
Material	Sheet steel
Surface finish	Zinc-plated
Supply includes	2 punched sections without mounting flanges 4 mounting brackets Assembly parts
Installation options	In VX on the inner mounting level, on the VX enclosure section In the VX SE, on the vertical enclosure section in conjunction with the VX adaptor rail Between two punched sections on the inner mounting level

© Rittal 2025 2

### **Features**

To fit	Enclosure type: VX VX SE Width/depth: 800 mm
Packs of	2 pc(s).
Net weight	1.454
Gross weight	1.92
Customs tariff number	73269098
EAN	4028177924512
ETIM 9	EC002620
ECLASS 8.0	27189234

© Rittal 2025 3