


# Rittal – The System.

Faster – better – everywhere.



## SV 9320 030 Busbar connector

State: 11/08 2015 (Source: [rittal.com/eg-en](http://rittal.com/eg-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9320.030 - Busbar connector

For connecting busbars, no drilling required.

## Features

Model No.	SV 9320.030
Product description	For connecting rectangular busbars, no drilling required.
Material	Top piece: Sheet steel, zinc-plated, passivated Contact plate: E-Cu, silver-plated
Connection type	Baying connection from enclosure to enclosure
To fit busbars	20 x 5 - 30 x 10
Packs of	3 pc(s).
Net weight	1.881
Gross weight	2.02
Copper weight (kg per piece)	0.35
PCF per pack (cradle-to-gate)	7.9 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Customs tariff number	85369010
EAN	4028177149830
ETIM 9	EC000713
ECLASS 8.0	27400606

## Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK

# Tender text

Busbar connector

Baying connectors for connecting rectangular busbars, no drilling required.

Design

Baying connection from enclosure to enclosure for busbars 20 x 5 - 30 x 10

System:

Rittal RiLine60