

Rittal – The System.

Faster – better – everywhere.



SV 9677.900 Connection adaptor

State: 03/08/2025 (Source: [rittal.com/sg-en](https://www.rittal.com/sg-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9677.900 - Connection adaptor

For the connection of round conductors. For bar systems with 185 mm centre-to-centre spacing.

Features

| | |
|---|--|
| Model No. | SV 9677.900 |
| Material | Chassis: Fibreglass-reinforced polyester Fire protection corresponding to UL 94-V0 |
| Colour | RAL 7035 |
| For bar systems with centre-to-centre spacing | 185 mm |
| Cable outlet | Top/bottom |
| Type of electrical connection | Screw M12 |
| Number of poles | 3-pole |
| Rated current max. | 800 A |
| Rated operating voltage | 690 V, 3~ |
| Note | When using components on busbars with contact hazard protection cover, the contact terminal must be used |
| Dimensions | Width: 100 mm Height: 665 mm |
| Connection of round conductors | 6 - 240 mm ² |
| To fit busbars | Height: 10 mm |
| Packs of | 1 pc(s). |
| Net weight | 4.5 |
| Gross weight | 5 |
| Copper weight (kg per piece) | 3.128 |
| Customs tariff number | 85369010 |
| EAN | 4028177705289 |
| ETIM 9 | EC001531 |

Features

| | |
|------------|----------|
| ECLASS 8.0 | 27370304 |
|------------|----------|

Approvals

| | |
|--------------|---|
| Explanations | Declaration of conformity Declaration of conformity UK |
|--------------|---|