Rittal – The System.

Faster – better – everywhere.





SK 3238.400 Blue e+ outlet filter

State: 25.8.2025 (Source: rittal.com/si-sl)



SK 3238.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the corresponding fan-and-filter unit to dissipate heat loss from enclosures, ventilate the enclosure and protect temperature-sensitive components. This is achieved through the direct infeed of ambient air, the temperature of which must be lower than the permissible internal temperature of the enclosure.







Features

| Model No. | SK 3238.400 |
|------------------|--|
| Design | wall-mounted EMC |
| Benefits | Easy filter changes, thanks to a new opening mechanism on the louvred grille Faster installation on the enclosure with optimised detent hooks Tool-free assembly |
| Colour | RAL 7035 |
| Supply includes | Outlet filter EMC filter mat |
| Mounting cut-out | Cut-out width: 124 mm Cut-out height: 124 mm |
| To fit Model No. | SK 3238.8xx |
| Dimensions | Width: 148.5 mm Height: 148.5 mm Depth: 34.2 mm |

© Rittal 2025 2

Features

| Protection category NEMA | Type 12 with chopped-fibre filter Type 3, 3R, 4, 4X with chopped-fibre filter and hose-proof hood |
|--------------------------------------|--|
| IP protection category to IEC 60 529 | IP 54 with chopped-fibre filter IP 56 with chopped-fibre filter and hose-proof hood |
| Packs of | 1 pc(s). |
| Net weight | 0.15 |
| Gross weight | 0.217 |
| Customs tariff number | 39269097 |
| EAN | 4028177998407 |
| ETIM 9 | EC002513 |
| ETIM 8 | EC002513 |
| ECLASS 8.0 | 27180706 |

Approvals

Approvals

UL + C-UL - FTTA

UR + C-UR (recognized)

© Rittal 2025 3