

Rittal – The System.

Faster – better – everywhere.



SK 3240.724

Ventilatorska in filtrirna enota Blue e+

State: 6.5.2026 (Source: rittal.com/si-sl)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3240.724 - Ventilatorska in filtrirna enota Blue e+

Popolna ventilatorska enota za montažo na različne površine brez uporabe orodja. Pretok zraka od 20 do 1160 m³/h, standardni razred zaščite IP 54.



Features

Št. Modela	SK 3240.724
Zasnova	stenska namestitev
Opis izdelka	Ventilatorsko-filtrirne enote z diagonalno tehnologijo ventilatorjev so tlačno bolj stabilne in zagotavljajo bolj enakomeren pretok zraka. Diagonalna smer pretoka zraka zagotavlja bolj enakomerno odvajanje toplote iz ohišja.
Prednosti	Največji pretok zraka zaradi nagubanega filtra, ki je vključen v dobavo Enostavna menjava filtra zaradi novega mehanizma odpiranja na lamelni rešetki Hitrejša namestitev na ohišje z optimiziranimi zaskočnimi zatiči Tehnologija diagonalnih ventilatorjev zagotavlja bolj enakomerno in konstantno prezračevanje ohišja zaradi izboljšane stabilnosti tlaka Sestavljanje brez orodja
Material	Plastika
Barva	RAL 7035
Obseg dobave	Celotna enota, pripravljena za montažo, vključno z nagubanim filtrom
Ventilator	Diagonal, DC motor

Features

Pretok zraka, neoviran pretok zraka (z nagubanim filtrom)	Z DC: 218 m ³ /h
Pretok zraka z ustreznim izhodnim filtrom, vključno z nagubanim filtrom	Z DC: 191 m ³ /h
Pretok zraka, neoviran pretok zraka (s filtrom iz sesekljanih vlaken)	Z DC: 175 m ³ /h
Pretok zraka z ustreznim izhodnim filtrom, vključno s filtrom iz sesekljanih vlaken	Z DC: 130 m ³ /h
Nazivna delovna napetost	24 V (DC)
Poraba energije Pel	Z DC: 10,1 W
Maks. nazivni tok	Z DC: 0,42 A
Mere	Širina: 255 mm Višina: 255 mm Globina: 129 mm
Globina namestitve	108 mm
Izrez za montažo	Širina izreza: 224 mm Višina izreza: 224 mm
IP razred zaščite po IEC 60 529	IP 54 with chopped-fibre filter/pleated filter IP 55 with pleated filter and absorber mat IP 56 with chopped-fibre filter/pleated filter and hose-proof hood
Razred zaščite NEMA	Type 12 with chopped-fibre filter/pleated filter Type 3, 3R, 4, 4X with chopped-fibre filter/pleated filter and hose-proof hood
Predvarovalka	Miniaturni odklopnik/varovalka: 2 A
Opomba	Pri ventilatorsko-filtrirni enoti 3237.XXX se električni priključek izvede preko dveh enojnih žic (dolžine približno 300 mm) na enoti, pri vseh drugih ventilatorsko-filtrirnih enotah pa se uporablja brezvijačna vzmetna sponka
Delovno temperaturno območje	-30 °C...55 °C
Temperaturno območje shranjevanja	-30 °C...70 °C

Features

Stopnja hrupa	Z DC: 48 dB(A)
Paketi	1 pc(s).
Neto teža	1,97 kg
Bruto teža	2,178 kg
Carinska tarifna številka	84145915
ETIM 9	EC000320
ETIM 8	EC000320
ECLASS 8.0	27180716
Opis izdelka	SK Blue e+ fan-and-filter unit, 218 m ³ /h, 24 V (DC), WHD 255 x 255 x 129 mm, RAL 7035

Approvals

Approvals	30 - KC Korea UL + C-UL - FTTA UR + C-UR (recognized)
Explanations	Declaration of conformity