

Rittal – The System.

Faster – better – everywhere.



SK 3301.960

Cooling medium (ready-mixed)

State: 1.4.2026 (Source: rittal.com/si-sl)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3301.960 - Cooling medium (ready-mixed) For chillers and air-water heat exchangers

As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection.

Features

| | |
|-----------------------------|--|
| Model No. | SK 3301.960 |
| Product description | As well as protecting against frost, this cooling medium also serves to inhibit bacterial growth and provide optimum corrosion protection. |
| Contents | 10 l |
| Antifreeze/water mixture | 1 : 4 |
| Delivery form | Canister |
| Rifrost | Standard |
| Operating temperature range | -10 °C...60 °C |
| Packs of | 1 pc(s). |
| Net weight | 9,5 kg |
| Gross weight | 10 kg |
| Customs tariff number | 38200000 |
| ETIM 9 | EC001243 |
| ETIM 8 | EC001243 |
| ECLASS 8.0 | 23061202 |
| Product description | SK Cooling medium for chillers, glycol/water mixture : 1:4, container: 10 l, standard |

Tender text

RiFrost: Standard 10 l for water circuits

Apart from the recooling systems for oil and emulsion, all other recooling systems are only suitable for the cooling of water or a water/glycol mixture.

As well as protecting against frost, these also serve to impair bacterial growth and achieve optimum corrosion protection.

Technical data

RiFrost: Standard

Glycol/water mixture: 1:4

Container: 10 l

(Safety data sheets under Downloads)