

Rittal – The System.

Faster – better – everywhere.



RX 9360.000

RiLineX buying set

State: 3.7.2026 (Source: rittal.com/si-sl)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9360.000 - RiLineX baying set za ploščo

RiLineX baying connector set for the 3-pole complete board, for use with 550 A and 800 A. Comprising a busbar connector and contact hazard protection cover. For simple baying of boards between two bayed VX enclosures, no drilling required.



Features

Št. Modela	RX 9360.000
Opis izdelka	Za priklop vodil med ohišji brez vrtanja.
Prednosti	Time savings thanks to fully digital product data Reduced assembly time thanks to pre-assembled complete board Tested short-circuit resistance up to 65 kA Suitable for applications up to 1000 V AC and up to 1500 V DC Tested and certified to IEC and UL Simple extension and baying
Material	Konzola: jeklena pločevina, pocinkano Kontaktna plošča: E-Cu, pocinkano Sprednji pokrov: poliamid (PA 6) Protipožarna zaščita v skladu z UL 94
Barva	RAL 35745
Obseg dobave	3 priključki zbiralnih sponk 1 sprednji pokrov 1 izolacijska plošča
IP razred zaščite po IEC 60 529	IP 2XB

Features

Standardi	IEC 61 439-1/-2 UL 508
Maks. nazivni tok	780 A
Nazivni tok (UL)	780 A
Električne nazivne vrednosti UL (SCCR)	52.5 kA - 600 V, RMS, unprotected 100 kA - 600 V, Fuse Class L max. 1600 A, JDDZ/7 100 kA - 600 V, circuit breaker max. 600 A, DIVQ/7 100 kA - 480 V, circuit breaker max. 800 A, DIVQ/7 65 kA - 600 V, circuit breaker max. 800 A, DIVQ/7
Nazivna impulzna vzdržna napetost U _{imp}	12 kV
Rated voltage	1.000 V AC 1.500 V DC 600 V AC (UL) 600 V DC (UL)
Rated insulation voltage U _i	1.000 V AC 1.500 V DC
Rated impulse withstand current	103 kA 115,5 kA
Rated short-term withstand current/t	45 kA/200 ms 52,5 kA/500 ms
Kategorija prenapetosti	4
Stopnja kontaminacije	3
Število polov	3-pole
Za model št.	9360004 9360008 9360024 9360028 9360064 9360068 9360084 9360088
Osnovna frekvenca	50...60 Hz

Features

Vlažnost okolice (brez kondenzacije)	10...90 %
Za namestitev zbiralnih sponk	30 x 5/10
Delovno temperaturno območje	-5 °C...55 °C
Mere	Širina: 154 mm Višina: 240 mm Globina: 77 mm
Fire load	5,933 MJ/m ²
Paketi	1 pc(s).
Neto teža	1,88 kg
Bruto teža	1,924 kg
Teža bakra (kg na kos)	0,297
PCF na paket (od zibelke do vrat)	10,32
Carinska tarifna številka	85369010
ETIM 9	EC002270
Opis izdelka	RiLineX baying connector set for the complete board, for use with 550 A and 800 A. Comprising a busbar connector and contact hazard protection cover. For simple, no-drill baying of boards between two bayed enclosures. Baying connectors are included with the supply.

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity PCF-declaration