

# Rittal – The System.

Faster – better – everywhere.



## TS 8800.130 Montážna výstuha

State: 23.5.2026 (Source: [rittal.com/sk-sk](http://rittal.com/sk-sk))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 8800.130 - Montážna výstuha pre VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



## Features

Obj. č.	TS 8800.130
Technické údaje	Dierovanie Ø 4,5 mm v rozmerovom rastru 25 mm
Materiál	Oceľový plech
Povrch	Pozinkovaný
Rozsah dodávky	Vrátane upevňovacieho materiálu
Dĺžka	590 mm
Možnosti montáže VX SE	V skrini šírky/hĺbky 600 mm, na vnútornej montážnej rovine
Možnosti montáže AX	V skrini šírky 700 mm a v skrini šírky 600 mm, v spojení s lištou pre vnútornú montáž AX
Možnosti inštalácie AX z nehrdzavejúcej ocele	V šírke rozvádzača 600 mm
Možnosti montáže PC	V skrini šírky 600 mm, na vnútornej montážnej rovine
Možnosti montáže IW	V skrini šírky/hĺbky 600 mm, na vnútornej montážnej rovine
Možnosti montáže TS	V skrini šírky/hĺbky 600 mm, na vnútornej montážnej rovine
Možnosti montáže TP	V podstavci pultu TP a kompaktného pultu, hĺbka rozvádzača 600 mm, v spojení s lištou pre vnútornú montáž pre TP, kompaktná rozvážacia skriňa HD

# Features

---

Vhodné pre	Typ skrine: TS VX SE TP PC IW AX Šírka/hĺbka: 600 mm
Balenie	20 pc(s).
Netto hmotnosť	5,86 kg
Brutto hmotnosť	6,165 kg
PCF per pack (cradle-to-gate)	27,96 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
Číslo colnej sadzby	73269098
ETIM 9	EC002620
ECLASS 8.0	27189261
Popis výrobku	TS montážna výztuha, pre TS, VX SE, TP, pre vnútornú montážnu rovinu: pre š/h: 600 mm, d: 590 mm

# Approvals

---

Explanations	PCF-declaration
--------------	-----------------