

Rittal – The System.

Faster – better – everywhere.



RX 9362.250

RiLineX NH fuse-switch disconnecter

State: 14.6.2026 (Source: rittal.com/sk-sk)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



RX 9362.250 - RiLineX NH fuse-switch disconnecter

RiLineX NH fuse-switch disconnecter in size 2 for 60 mm busbar systems. The cover can be locked and prepared for a lead seal. It also has visual fuse monitoring. Integrated measuring points on the cover ensure safe voltage testing. NH fuse-switch disconnecters have a park position to make maintenance easier. Box terminal connection to connect round conductors ranging from min. 120 to max. 300 mm². Cable outlet can be at the top or bottom, as required.



Features

| | |
|--------------------------------------|---|
| Obj. č. | RX 9362.250 |
| Prevedenie | For 60 mm busbar systems |
| Výhody | Cover: can be locked and prepared for a lead seal Voltage test through separate opening Tool-free changeover of the cable outlet Park position for simpler maintenance work All variants also available with electronic fuse monitoring |
| Materiál | Polyamid (PA 6) Ochrana proti požiaru zodpovedá UL 94 Kontaktové dráhy: elektrolytická meď, postriebrená |
| Farba | RAL 9005 RAL 35745 |
| Pre prípojnicové systémy s rozstupom | 60 mm |
| Vývod vodičov | Top/bottom |
| Spôsob (elektrického) pripojenia | Box terminal |
| Poistkové vložky | NH 2 |
| Menovité prevádzkové napätie | 690 V AC |

Features

| | |
|---|---|
| Pre veľkosť NH | 2 |
| Test specification | IEC/DIN EN 60 947-3 DIN EN 60 269-2 (poistkové vložky) |
| Rozmery | Šírka: 208,5 mm Výška: 298,6 mm Hĺbka: 134,6 mm |
| Rozsah prevádzkových teplôt | -5 °C...35 °C |
| Rozsah skladovacích teplôt | -25 °C...70 °C |
| Vhodné pre prípojnice | 15 x 5/10 20 x 5/10 30 x 5/10 |
| Vhodné pre prípojnicový systém | RiLineX RiLine60 |
| Počet pólov | 3-pole |
| Stupeň znečistenia | 3 |
| Stupeň krytia IP podľa normy IEC 60 529 | IP 2XB |
| Fire load | 50,96 MJ/m ² |
| Stratový výkon max. | 98 W |
| Balenie | 1 pc(s). |
| Netto hmotnosť | 4,25 kg |
| Brutto hmotnosť | 4,355 kg |
| Podiel medi (kg / ks) | 1,75 |
| PCF per pack (cradle-to-gate) | 28,84 |
| Číslo colnej sadzby | 85369095 |
| ETIM 9 | EC001040 |

Features

Popis výrobku

RiLineX NH fuse-switch disconnecter in size 2 for 60 mm busbar systems. The cover can be locked and prepared for a lead seal. It also has visual fuse monitoring. Integrated measuring points on the cover ensure safe voltage testing. NH fuse-switch disconnectors have a park position to make maintenance easier. Box terminal connection to connect round conductors ranging from min. 120 to max. 300 mm². Cable outlet can be at the top or bottom, as required.

Approvals

Approvals

CQC-CCC

Explanations

Declaration of conformity
PCF-declaration