## Rittal – The System.

Faster – better – everywhere.





## FT 2735.250 - System windows for VX, TS, VX SE

To conceal display and operating instruments or cut-outs, and to protect against dirt and liquids as well as unauthorised access.







#### **Features**

Model No.	FT 2735.250
Design	30 section
Product description	To conceal display and operating instruments or cut-outs, and to protect against dirt and liquids as well as unauthorised access.
Material	Extruded aluminium section with die-cast zinc corner pieces and single-pane safety glass.
Surface finish	Base frame: Powder-coated on the outside in RAL 7035 Hinge and lock section: Natural-anodised
Value base frame	Made from single-pane safety glass: High level of resistance to solvents and scratches, anti-static, reduced risk of injury if broken. Standard double-bit lock insert may be exchanged for lock inserts 27 mm, type A, and/or for lock system Ergoform-S (except H = 270 mm).  Hinge with 180° opening angle, easily inserted.

© Rittal 2025

### **Features**

Easily screw-fastened to the door thanks to modified dimensions (tubular door frame may be used as a drilling template). Readily height-adjustable. Stabilises the door cut-out. Conceals the cut edge. There is no dirt on the seal, the glass is protected from being lifted out, dirt cannot drop inside, and moisture cannot run behind the window when opening. Frame section height 30 mm or 60 mm
IP 54
Standard double-bit lock insert may be exchanged for lock inserts 27 mm, type A, and/or for lock system Ergoform-S (except H = 270 mm).  Not suitable for outdoor siting
Enclosure type: VX TS VX SE Width: = 800 mm
Width: 700 mm Height: 670 mm Depth: 47 mm
Viewing window width: 563 mm Viewing window height: 598 mm
33 mm
1 pc(s).
6.853
7.214
76101000
4028177476370
EC002527
EC002527
27182301

© Rittal 2025 3

# **Approvals**

Certificates

Protection category

© Rittal 2025