

**Rittal – The System.**

Faster – better – everywhere.



**SV 3528.000**

**PLS special busbars E-Cu**

State: 22.05.2026 (Source: [rittal.com/ua-en](http://rittal.com/ua-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 3528.000 - PLS special busbars E-Cu

Lengths range from 495 mm to 2400 mm.



## Features

Model No.	SV 3528.000
Material	E-Cu
Bar thickness	10 mm
Rated current (max.)	1,368 A
Cross-section	900 mm <sup>2</sup>
Note	May be cut individually to required length
Busbar type	Busbar E-Cu
To fit busbar system	PLS 1600
To fit Model No.	9342.000 9342.004 9342.050
Dimensions	Length: 695 mm
To fit	Width: = 800 mm
Packs of	3 pc(s).

# Features

---

Net weight	16.86 kg
Gross weight	16.86 kg
Copper weight (kg per piece)	5.62
Customs tariff number	74071000
ETIM 9	EC001522
ETIM 8	EC001522
ECLASS 8.0	27370303
Product description	SV PLS special busbar E-Cu, L: 695 mm, PLS 1600, bar thickness: 10 mm, 900 mm <sup>2</sup> bar cross-section

# Approvals

---

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK

# Tender text

PLS special busbar E-Cu 1600 A  
Bar thickness: 10 mm  
Rated current: 1600 A  
Cross-section: 900 mm<sup>2</sup>  
Length: 695 mm  
Enclosure width: 800 mm  
(Rittal PS/TS/ES enclosure systems)