

Rittal – The System.

Faster – better – everywhere.



AS 4050.749 Wire end ferrules

State: 08.09.2025 (Source: rittal.com/ua-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4050.749 - Wire end ferrules on a reel

With plastic collar.

Features

| | |
|--------------------------|---|
| Model No. | AS 4050.749 |
| Design | for wire processing machines |
| Product description | With plastic collar. |
| Technical specifications | Heat-resistant to 105 °C |
| Material | E-Cu, galvanic tin-plated Plastic collar: Polypropylene |
| Colour | Black |
| To fit | Enclosure type: Crimping machine RC Crimping machine R8 Crimping machine R8 E |
| Length | 8 mm |
| AWG | 16 |
| Internal diameter | 3.5 mm |
| For cross-section | 1.5 mm ² |
| DIN colour code | Yes |
| Note | UL-certified in conjunction with the relevant tools, such as crimping machines. |
| Delivery form | Taped |
| Packs of | 5,000 pc(s). |
| Net weight | 5 |
| Gross weight | 0.722 |
| Customs tariff number | 85369010 |
| EAN | 4028177805170 |
| ETIM 9 | EC000005 |

Features

| | |
|------------|----------|
| ETIM 8 | EC000005 |
| ECLASS 8.0 | 36659290 |

Approvals

| | |
|-----------|--------------------------|
| Approvals | UL + C-UL (listed) UR |
|-----------|--------------------------|