


Rittal – The System.

Faster – better – everywhere.



AS 4055.460

Hole punch, heavy connectors

State: 06.07.2025 (Source: rittal.com/ua-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.460 - Hole punch, heavy connectors for sheet steel

For punching rectangular cut-outs for connectors

Features

| | |
|--|---|
| Model No. | AS 4055.460 |
| Product description | For punching rectangular cut-outs for connectors. The hole punch is operated with a hydraulic punch. |
| Benefits | With side ejector for the waste No jamming of the die When the die and stamp are compressed, the mounting holes for connectors are marked on the metal sheet between them |
| Supply includes | Female dies Male dies Tension bolts Lock nut |
| Machinable material | Sheet steel |
| Maximum machinable material thickness, sheet steel | 2 mm |
| □ punch | 36 x 52 mm |
| Packs of | 1 pc(s). |
| Net weight | 2.8 |
| Gross weight | 2.87 |
| Customs tariff number | 82073010 |
| EAN | 4028177808515 |
| ETIM 9 | EC000156 |
| ETIM 8 | EC000156 |
| ECLASS 8.0 | 21049047 |