Rittal – The System.

Faster – better – everywhere.





TS 8100.235 Side panel, screw-fastened, sheet steel

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 30.08.2025 (Source: rittal.com/ua-en)

POWER DISTRIBUTION

RITTAL

FRIEDHELM LOH GROUP

ENCLOSURES

TS 8100.235 - Side panel, screw-fastened, sheet steel for TS, TS IT

Side panels, screw-fastened, sheet steel, for TS.

Features

Model No.	TS 8100.235
Benefits	Automatic potential equalisation and higher EMC protection due to enclosure panel holders with earthing insert Easy positioning with the location aid
	Earthing bolt with contact surface
Material	Sheet steel, 1.5 mm
Surface finish	Dipcoat-primed, powder-coated on the outside
Colour	RAL 7035
Supply includes	Assembly parts
Note	Enclosure panel holders may optionally be fitted from the inside or outside of the enclosure Area available for population: External dimension – 100 mm
To fit	Enclosure type: TS TS IT Height: 2,000 mm Depth: 1,000 mm
IP protection category to IEC 60 529	IP 55
Basic material	Sheet steel
Packs of	2 pc(s).
Net weight	46.8
Gross weight	48
Customs tariff number	94039910
EAN	4028177233720

Features

E-Number Sweden	E7239710
ETIM 9	EC002524
ECLASS 8.0	27182101

Tender text

Side panel, screw-fastened, for TS Easy positioning on the frame with the location aid. The enclosure panel holders with earthing insert ensure automatic potential equalisation and higher EMC protection. They may optionally be fitted from the inside or outside of the enclosure. When using TS side panel hinges an opening angle of 180° is possible.

Material: 1.5 mm sheet steel

Area available for population: External dimension 100 mm

Protection category: IP 55

Surface finish: Dipcoat-primed, powder-coated in textured RAL 7035 on the outside

For enclosure dimensions: H: 2000 mm D: 1000 mm