


# Rittal – The System.

Faster – better – everywhere.



## KEL 9305.000 Ex enclosures

State: 12.05.2026 (Source: [rittal.com/ua-en](http://rittal.com/ua-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# KEL 9305.000 - Ex enclosures stainless steel, empty enclosure with screw-fastened cover

Ex enclosure with screw-fastened cover, stainless steel



## Features

|                                 |   |
|---------------------------------|---|
| Model No.                       | KEL 9305.000  |
| Design                          | Ex enclosures   |
| Applications                    | Zone 1 and 2 or 21 and 22 to 2014/34/EC<br>Ambient temperature range: -30 °C...+80 °C<br>The specified temperatures may be limited by the installed equipment<br>Explosion protection category to EN 60 079: Equipment protection thanks to increased safety (Ex e), equipment protection thanks to enclosure (Ex tb) |
| Material                        | Enclosure: Stainless steel 1.4301 (AISI 304)<br>Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal   |
| Surface finish                  | Enclosure: Brushed, grain 400, peak-to-valley height < 0.8 µm   |
| Supply includes                 | Enclosure<br>Cover  |
| Dimensions                      | Width: 400 mm<br>Height: 200 mm<br>Depth: 120 mm  |
| Certificate IEC EX PTB 09.0033U | Yes   |
| Certificate PTB 03 ATEX 1013U   | Yes   |
| Basic material                  | Stainless steel 1.4301 (AISI 304)   |

# Features

---

|                                     |  |
|-------------------------------------|--|
| IP protection category to IEC 60529 | IP 66  |
| Packs of                            | 1 pc(s).   |
| Net weight                          | 3.4 kg   |
| Gross weight                        | 3.6 kg   |
| Customs tariff number               | 94032080   |
| ETIM 9                              | EC002503   |
| ECLASS 8.0                          | 27180502   |
| Product description                 | KEL Ex enclosure, WHD: 400x200x120 mm, Stainless steel 1.4301, without mounting plate, Empty enclosure with screw-fastened cover |

# Approvals

---

|              |  |
|--------------|--|
| Approvals    | ATEX<br>ATEX QA<br>CQC-CCC<br>IECEX<br>IECEX QAR |
| Explanations | Attestation of Conformity                        |