

Rittal – The System.

Faster – better – everywhere.



SV 9686.000 Busbar support

State: 02.06.2026 (Source: rittal.com/ua-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9686.000 - Busbar support for busbar baying (roof section)

For baying busbar systems from enclosure to enclosure in the roof section.

Features

| | |
|-------------------------------------|---|
| Model No. | SV 9686.000 |
| Product description | For baying 3- or 4-pole flat copper busbar systems from enclosure to enclosure in the roof section. |
| Material | Duroplastic Fire protection corresponding to UL 94-V0 |
| Colour | Similar to RAL 9005 |
| Supply includes | Assembly parts |
| To fit busbars | 30 x 10 |
| Centre-to-centre spacing of busbars | 80 mm |
| Assembly instruction | For the installation of max. 4 busbars (sub-conductors) per phase Cage nut (M8) 4165.500 is required to attach the busbar support to the enclosure section |
| Packs of | 2 pc(s). |
| Net weight | 3.8 kg |
| Gross weight | 3.88 kg |
| Customs tariff number | 85469010 |
| ETIM 9 | EC001166 |
| ECLASS 8.0 | 27400607 |
| Product description | SV busbar holder (baying), 4-pole, 80 mm, for E-Cu 30 x 10 mm, duroplastic, fire protection in accordance with UL 94-V0 |

Approvals

Approvals

DNV
Lloyds Register

Explanations

Declaration of conformity UK