Rittal - The System.

Faster – better – everywhere.



SK 3286.870 Air duct system

State: 24/08/2025 (Source: rittal.com/uae-en)



SK 3286.870 - Air duct system for roof-mounted cooling units and roof-mounted air-water heat exchangers

The air duct system allows cold air to be routed directly to specific areas of the enclosure. This effectively eliminates the risk of air short-circuits due to self-ventilated installed devices. The shallow ducts can be cut to the desired length.

Features

Model No.	SK 3286.870		
Product description	Cold air may be routed directly to specific areas of the enclosure using the air duct system. The risk of air short circuits due to self-ventilated installed devices is therefore eliminated. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length.		
Material	Flame-resistant plastic to DIN 4102/B1		
Colour	RAL 7035		
Supply includes	Shallow duct		
	Compensating hose (length approx. 1 m)		
Note	Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unmay be reduced, depending on the application in question. For devices 3359/3382, the air duct adaptor 3286.840 is additionally required.		
To fit Model No.	3209 3210 3273 3359 3382 3383 3384		
Packs of	1 pc(s).		
Net weight	3.08		

© Rittal 2025 2

Features

Gross weight	3.16
Customs tariff number	39269097
EAN	4028177325449
ETIM 9	EC011444
ETIM 8	EC011444
ECLASS 8.0	22410601

Approvals

Certificates	EAC	

© Rittal 2025 3