

Rittal – The System.

Faster – better – everywhere.



SK 3304.542

TopTherm wall-mounted cooling unit Blue e

State: 13/03/2026 (Source: rittal.com/uae-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3304.542 - TopTherm wall-mounted cooling unit Blue e 0.3 - 4 kW

Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W). Available in the special formats "horizontal" and "flat".

Features

Model No.	SK 3304.542
Design	wall-mounted
Product description	Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W).
Benefits	May be linked to the IoT interface via Blue e IoT adaptor for cooling units from 500 W cooling output with e-Comfort controller
Material	Sheet steel
Colour	RAL 7035
Supply includes	Condenser with hydrophobic RiNano coating Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts Integral electric condensate evaporation
Total cooling output to DIN EN 14511	Cooling output L35 L35/50 Hz: 1.1 kW Cooling output L35 L35/60 Hz: 1.25 kW Cooling output L35 L50/50 Hz: 0.88 kW Cooling output L35 L50/60 Hz: 0.99 W
Rated operating voltage	400 V, 3~, 50 Hz 460 V, 3~, 60 Hz
Rated current max.	At 50 Hz: 2.2 A At 60 Hz: 2.1 A
Start-up current max.	At 50 Hz: 11.5 A At 60 Hz: 12.7 A

Features

Energy efficiency ratio (EER) 50/60 Hz L35 L35	Refrigeration factor L35 L35 (EER) 50 Hz: 1.83
--	--

Design	wall-mounted
--------	--------------

Protection category to IEC 60 529	External circuit IP 34 Internal circuit IP 54
-----------------------------------	--

Protection category NEMA	UL Type 12
--------------------------	------------

Refrigerant/cooling medium	Refrigerant: R-513A Quantity: 0.325 kg Global Warming Potential (GWP): 631 CO2 equivalent (CO2e): 0.46 t
----------------------------	---

Temperature control	e-Comfort controller (factory setting +35 °C)
---------------------	---

Operating temperature range	10 °C...55 °C
-----------------------------	---------------

Storage temperature range	-40 °C...70 °C
---------------------------	----------------

Setting range	20 °C...55 °C
---------------	---------------

Power consumption Pel	Power consumption L35 L35/50 Hz: 0.76 kW Power consumption L35 L35/60 Hz: 0.93 kW
-----------------------	--

Permissible operating pressure (p. max.)	25 bar
--	--------

Pre-fuse	Motor circuit-breaker: 6.3...10 A
----------	-----------------------------------

Packs of	1 pc(s).
----------	----------

Net weight	50.001 kg
------------	-----------

Gross weight	50.001 kg
--------------	-----------

Customs tariff number	84158200
-----------------------	----------

ETIM 9	EC000855
--------	----------

ETIM 8	EC000855
--------	----------

ECLASS 8.0	27180704
------------	----------

Approvals

Approvals

Certificates

EAC

Explanations

Declaration of conformity