

Rittal – The System.

Faster – better – everywhere.



DK 7030.200 CMC III CAN bus access

State: 23/05/2026 (Source: rittal.com/uae-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7030.200 - CMC III CAN bus access

For connecting one handle and one reader unit to monitor a door.

Features

| | |
|---------------------|---|
| Model No. | DK 7030.200 |
| Design | With integral infrared access sensor. For connecting one handle and/or one CMC III reader unit. |
| Product description | The CMC III CAN bus access allows electromagnetic handles and read systems to be connected to the CMC III system or IoT interface. One handle and optionally one CMC III read system can be connected to one CMC III CAN bus access. The CMC III CAN bus access has an integral infrared sensor to monitor the door status. The electromagnetic handle is monitored and controlled by the CMC III. Handles can be released by numerical codes or transponder cards if a read system is connected. Up to 16 door handles can be managed simultaneously with one read system. |
| Benefits | Fast connection and automatic detection via plug & play Power is supplied via the CAN-BUS interface. |
| Applications | Monitoring and controlling electromagnetic handles on enclosures in the fields of IT, industry and buildings technology. |
| Function principle | Settings can be made via the CMC III processing unit or IoT interface Status display via integral LED The current measurements can be called up via the CMC III interface or the IoT interface using the browser, SNMP or OPC-UA, and adjustments made Automatic alarm messages by e-mail, text or SNMP trap when a limit value is exceeded |
| Material | Plastic Front: Smooth Enclosure: Textured |
| Colour | Enclosure: RAL 7035 Front: RAL 9005 |

Features

| | |
|--|--|
| Supply includes | CMC III CAN bus access Installation and Short User's Guide Assembly parts for mounting in the enclosure Mounting clips for support rails Assembly parts for surfaces Assembly parts Assembly parts for mounting on the enclosure |
| Interface bus system | 2 x RJ45 CAN bus |
| Interfaces | RJ12 Flat-pin connector for CMC III reader units |
| No. of participants per IoT interface (max.) | 16 |
| No. of participating PU compact (max.) | 2 |
| No. of participating PU (max.) | 16 |
| Dimensions | Width: 110 mm Height: 30 mm Depth: 40 mm |
| Operating temperature range | 0 °C...55 °C |
| Ambient humidity (non-condensing) | 5...95 % |
| Packs of | 1 pc(s). |
| Net weight | 0.2 kg |
| Gross weight | 0.212 kg |
| Customs tariff number | 85311095 |
| ETIM 9 | EC002627 |
| ECLASS 8.0 | 27189253 |
| Product description | DK CMC III CAN-Bus access, WHD: 110x30x40 mm, 2 x RJ45 CAN-Bus, RJ12 |

Approvals

Approvals

UL + C-UL (listed)

Explanations

Manufacturer's declaration

Declaration of conformity

Tender text

7030.200

CMC III CAN bus access

Packs of 1

Compact plastic housing with ventilated front in RAL 9005.

Housing in RAL 7035,

The sensor has two RJ45 connections with an integrated CAN bus. The sensor is automatically detected by the

CMC III system, the Processing Unit, and is provided with a sequential number in the bus sequence. Integrated multi-colour LED as status display.

The unit contains an infrared access sensor, an interface for a CMC III read system and an interface for an electro-mechanical comfort handle TS 8.

The infrared access sensor indicates whether the rack door is open or closed. A read system can be used to enter the codes for door release. Via a connected electric handle the door can be released and the door handle can be monitored.

Connection accessories:

7030.220 CMC III coded lock

7030.230 CMC III transponder reader

7320.700 Electromagnetic Ergoform-S

7320.721 Electromagnetic TS8 handle
with master

key function with and without CCP

7320.730 Universal lock

7320.950 Handle system for
universal installation

The access authorisation to the enclosure can be set via the software for the CMC III Processing Unit. The power supply is ensured by connection to the CAN bus for the Processing Unit.

Technical specifications:

Mode of operation: Optical

Transmitter: Infrared diode

Receiver: Infrared receiver

Interfaces: 1 CMC III reader unit

RJ12 interfaces: 1 handle

CAN bus jacks RJ45: 2

Protection category: IP 30 to IEC 60 529

Temperature application range:

0 °C to 55 °C

Humidity range:

5% to 95% relative humidity, non-condensing

WxHxD: 110 x 30 x 40 mm

Included in the pack: Sensor, quick reference guide and universal mounting set