

Faster – better – everywhere.





RX 9360.104 RiLineX baying set

CLIMATE CONTROL

State: 10/09/2025 (Source: rittal.com/uae-en)

POWER DISTRIBUTION



SOFTWARE & SERVICES

IT INFRASTRUCTURE

FRIEDHELM LOH GROUP

ENCLOSURES

RX 9360.104 - RiLineX baying set for basic module

RiLineX baying set, long variant, for board baying between two bayed VX enclosures (section baying). Variant including contact hazard protection cover, front and rear. The set is supplied without busbar connectors (9365013). These are available as accessories.

Features

Model No.	RX 9360.104
Benefits	Scalable system lengths with basic modules
	Simple assembly
	Scalable rated currents thanks to variable busbar cross-sections
	Tested short-circuit resistance up to 65 kA
	Suitable for applications up to 1000 V AC and up to 1500 V DC
	Extensive range of system accessories
	Contact hazard protection up to IP 2XB, upgradable to IP 3X
Material	Polyamide (PA 6)
	Fire protection corresponding to UL 94
Colour	RAL 35745
Supply includes	Board end element, left and right
	Board module cover
	Board module base plate
	Assembly parts
To fit Model No.	9365.013
Packs of	2 pc(s).
Net weight	1.46
Gross weight	1.481
Customs tariff number	85369010
EAN	4028177997301
ETIM 9	EC002270

Approvals

Approvals

UL + C-UL (listed)

Explanations

Declaration of conformity