

Faster – better – everywhere.





RX 9360.707 RiLineX component support

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

State: 22/08/2025 (Source: rittal.com/uae-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

RX 9360.707 - RiLineX component support without contact system

RiLineX component support in width 54 mm for RiLineX and 60 mm busbar system platforms, without contact system. Ideal for securing wider equipment onto the board.



Features

Model No.	RX 9360.707
Design	without contact system
Benefits	For mounting equipment for top hat rail installation, e.g. motor
	starter
	Simple clip locking for support rails
	Optional anti-slip guard
	Coordinated accessories reduce the number of different items required
	Snap-on mounting and simple adjustment for busbar thickness
	(5/10 mm)
Material	Polyamide (PA 6)
	Fire protection corresponding to UL 94
Colour	RAL 9005
	RAL 35745
For bar systems with centre-to-	60 mm
centre spacing	
Dimensions	Width: 54 mm
	Height: 240 mm
	Depth: 37 mm

Features

To fit busbars	15 x 5/10
	20 x 5/10
	30 x 5/10
To fit busbar system	RiLineX
	RiLine60
Number of poles	3-pole
Support rails Qty	1
Rated voltage	690 V AC
	600 V AC (UL)
	600 V DC (UL)
Packs of	4 pc(s).
Net weight	1.26
Gross weight	1.278
Customs tariff number	85369095
EAN	4028177997042
ETIM 9	EC001531

Approvals

Approvals

UL + C-UL (listed)

Explanations

Declaration of conformity