Rittal – The System.

Faster – better – everywhere.





VX 9666.966 Bayed enclosure system VX25

State: 26/07/2025 (Source: rittal.com/uae-en)



VX 9666.966 - Bayed enclosure system VX25 Distribution enclosure

Baying systems VX as distribution enclosures, prepared for ISV installation modules







Features

Model No.	VX 9666.966
Material	Sheet steel
Surface finish	Enclosure frame: Dipcoat-primed
	Door(s), roof, rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Gland plates: Zinc-plated
Colour	RAL 7035
Supply includes	Enclosure frame
	Door(s)
	Door hinged on the right, may be swapped to the left
	Gland plates
	Rear panel
	Roof plate
	Lock: 3 mm double-bit
Number of doors	2
Note	For 600 mm wide distribution enclosures, please use VX basic
	enclosures
	For a base/plinth height of 200 mm, 2 packs each of plinth corner
	pieces, 100 mm and base/plinth trim panels, 100 mm are required

© Rittal 2025

Features

IP protection category to IEC 60 529	IP 55
Protection category NEMA	NEMA 12
Test specification	IEC 61 439-1/-2
Dimensions	Width: 1,100 mm Height: 2,000 mm Depth: 400 mm
Packs of	1 pc(s).
Net weight	111.65
Gross weight	118.6
PCF per pack (cradle-to-gate)	359.7 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177929777
ETIM 9	EC000214
ECLASS 8.0	27142409

Approvals

Approvals	Bureau Veritas DNV-GL
Certificates	Surface finish
Explanations	Declaration of conformity Declaration of conformity UK

© Rittal 2025 3