

Rittal – The System.

Faster – better – everywhere.



VX 9680.207

Bayed enclosure system VX25

State: 28/08/2025 (Source: rittal.com/uae-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 9680.207 - Bayed enclosure system VX25 Fuse-switch-disconnector enclosure

Baying systems for the distribution of electrical power with NH slimline fuse-switch disconnectors (ABB or Jean Müller).



Features

Model No.	VX 9680.207
Material	Sheet steel, 1.5 mm
Surface finish	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Gland plates: Zinc-plated
Colour	RAL 7035
Supply includes	Enclosure frame Door Roof plate Rear panel Gland plates Front trim panels Lock: 3 mm double-bit Compartment side panels Locating frame for disconnectors with fuses (brands ABB SlimLine/ Jean Müller SASIL)
Protection category to IEC 60 529	Up to IP 3X, depending on the panels

Features

Test specification	IEC 61 439-1/-2 IEC 61 641
Dimensions	Width: 1,200 mm Height: 2,000 mm Depth: 800 mm
Packs of	1 pc(s).
Net weight	149.6
Gross weight	166.2
PCF per pack (cradle-to-gate)	368.6 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177937079
ETIM 9	EC000261
ECLASS 8.0	27180101

Approvals

Certificates	Surface finish
Explanations	Declaration of conformity Declaration of conformity UK