

Faster - better - everywhere.





SV 9690.033 Energy storage frame

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 09/09/2025 (Source: rittal.com/uae-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

SV 9690.033 - Energy storage frame VX ESS

Enclosure frame with flexible interior fit-out. Ideal for efficient and modular energy storage installation.

Features

Model No.	SV 9690.033
Material	Enclosure frame: Sheet steel, 1.5 mm
	Mounting angles: Sheet steel, 2 mm
	Cross-member with mounting angle: Sheet steel, 3 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Mounting angles: Zinc-plated
	Cross-member with mounting bracket: Zinc-plated
Colour	RAL 7035
Supply includes	Enclosure frame
Dimensions	Width: 800 mm
	Height: 2,000 mm
	Depth: 800 mm
Packs of	1 pc(s).
Net weight	54
Gross weight	54.8
PCF per pack (cradle-to-gate)	137.31 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177044210
ETIM 9	EC000261