### Rittal - The System.

Faster – better – everywhere.





## SR 2338.235 Swing frame, large, with trim panel

State: 24/07/2025 (Source: rittal.com/uk-en)



# SR 2338.235 - Swing frame, large, with trim panel for TS, VX SE 800 mm wide enclosures

For 800 mm wide enclosures, 22 - 45 U, with trim panel, for mounting 482.6 mm (19") equipment.



#### **Features**

| Model No.            | SR 2338.235  |
|----------------------|--|
| Design               | 482.6 mm (19") level, centre   |
| Product description  | For mounting 482.6 mm (19") equipment.   |
| Material             | Sheet steel  |
| Surface finish       | Frame: Zinc-plated   |
|                      | Trim panel: Spray-finished   |
| Colour               | RAL 7035   |
| Supply includes      | Locking rod system with double-bit lock insert   |
|                      | Material for attaching   |
| Installation options | In the TS/SE with 180° opening angle   |
| Assembly instruction | Depending on the mounting situation, TS punched sections with mounting flanges 23 x 73 mm or 17 x 73 mm are required |
|                      |  |

© Rittal 2025 2

#### **Features**

| Note                  | For further installation options, see "Technical details" For two-door enclosures TS, SE with a height of 1800 or 2200 mm the next-smallest swing frame must be installed, due to collision with the lock |
|-----------------------|---|
| To fit                | Enclosure type: TS  VX SE  Width: = 800 mm  Height: ≥ 1,800 mm  |
| Units                 | 36 U  |
| To fit enclosure type | TS<br>VX SE   |
| Packs of              | 1 pc(s).  |
| Net weight            | 19.105  |
| Gross weight          | 20.11   |
| Customs tariff number | 94039910  |
| EAN                   | 4028177165182   |
| ETIM 9                | EC002620  |
| ETIM 8                | EC002620  |
| ECLASS 8.0            | 27189261  |

© Rittal 2025 3

#### Tender text

Large swing frame for network enclosure

36 U can be used for accommodating 482.6 mm (19") equipment. Torsionally stiff frame, welded from rectangular tube and triple folded support section. Load capacity up to 1500 N when standard hinges are used. Distance from inside edge of door to front edge of swing frame 100 mm, may be installed deeper on a pitch pattern of 25 mm. The swing frame must be fitted to the left / to the right depending on the installation depth of the equipment.

Installation position of equipment mounted in the centre.

Material: sheet steel

Surface finish: RAL 7035

for enclosure width: W: 800 mm

© Rittal 2025 4