Rittal – The System.

Faster – better – everywhere.





SK 3237.400 Blue e+ outlet filter

State: 3/12/2025 (Source: rittal.com/uk-en)



SK 3237.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the corresponding fan-and-filter unit to dissipate heat loss from enclosures, ventilate the enclosure and protect temperature-sensitive components. This is achieved through the direct infeed of ambient air, the temperature of which must be lower than the permissible internal temperature of the enclosure.







Features

SK 3237.400
wall-mounted EMC
Easy filter changes, thanks to a new opening mechanism on the louvred grille Faster installation on the enclosure with optimised detent hooks Tool-free assembly
RAL 7035
Outlet filter EMC filter mat
Cut-out width: 92 mm Cut-out height: 92 mm
SK 3237.8xx
Width: 116.5 mm Height: 116.5 mm Depth: 33.2 mm

© Rittal 2025 2

Features

Protection category NEMA	Type 12 with chopped-fibre filter
Trotoston outogory NEWIA	Type 3, 3R with chopped-fibre filter and hose-proof hood
IP protection category to IEC 60	IP 54 with chopped-fibre filter
529	IP 56 with chopped-fibre filter and hose-proof hood
Packs of	1 pc(s).
Net weight	0.075
Gross weight	0.154
Customs tariff number	39269097
EAN	4028177998414
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	UL + C-UL - FTTA
	UR + C-UR (recognized)

© Rittal 2025 3