

Faster – better – everywhere.





AS 4050.005 Smart Lifter

State: 29/08/2025 (Source: rittal.com/uk-en)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

AS 4050.005 - Smart Lifter

Lifting and transport device for enclosures and enclosure suites up 4.80 m long.



Features

Model No.	AS 4050.005
Product description	Lifting and transport device for enclosures and enclosure suites up to 4.80 m length.
Benefits	Supports simple mounting of base/plinths beneath enclosures Easy transportation of bayed enclosures in the workshop or at the installation site Flexible use for enclosures of different depths, thanks to adjustable
	forks Ergonomic working (lifting and lowering) with a torque crank
Taskaiselen aif i	
Technical specifications	Dimensions per trolley (W x H x D): 750 x 1100 x 400 mm
Function principle	Transportation of bayed enclosures up to a length of 4.80 m Transportable enclosure depths: 400, 500, 600, 800 mm
	Lifting of bayed enclosures up to a height of 230 mm and a weight of 1800 kg
Supply includes	2 transport trolleys
Load capacity	1,800 kg
Packs of	1 pc(s).
Net weight	180
Gross weight	195
Customs tariff number	84279000
EAN	4028177957558

Features

ETIM 9	EC001203
ETIM 8	EC001203
ECLASS 8.0	21079190

Approvals

Explanations

Declaration of conformity