

Rittal – The System.

Faster – better – everywhere.



AS 4050.005

Smart Lifter

State: 18/02/2026 (Source: rittal.com/uk-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4050.005 - Smart Lifter

Lifting and transport device for enclosures and enclosure suites up 4.80 m long.



Features

Model No.	AS 4050.005
Product description	Lifting and transport device for enclosures and enclosure suites up to 4.80 m length.
Benefits	<p>Supports simple mounting of base/plinths beneath enclosures</p> <p>Easy transportation of bayed enclosures in the workshop or at the installation site</p> <p>Flexible use for enclosures of different depths, thanks to adjustable forks</p> <p>Ergonomic working (lifting and lowering) with a torque crank</p>
Technical specifications	Dimensions per trolley (W x H x D): 750 x 1100 x 400 mm
Function principle	<p>Transportation of bayed enclosures up to a length of 4.80 m</p> <p>Transportable enclosure depths: 400, 500, 600, 800 mm</p> <p>Lifting of bayed enclosures up to a height of 230 mm and a weight of 1800 kg</p>
Supply includes	2 transport trolleys
Load capacity	1,800 kg
Packs of	1 pc(s).
Net weight	180 kg
Gross weight	195 kg
Customs tariff number	84279000
ETIM 9	EC001203

Features

ETIM 8	EC001203
ECLASS 8.0	21079190
Product description	Lifting and transport device for enclosures and enclosure suites. Supports simple mounting of base/plinths beneath enclosures as well as flexible transportation of complete switchgear systems up to 1.8 t. Adjustable forks enable the transportation of VX enclosures with depths of 400, 500, 600 and 800 mm.

Approvals

Explanations	Declaration of conformity
--------------	---------------------------