

# Rittal – The System.

Faster – better – everywhere.



## AS 4050.456 Crimping machine RC

State: 13/05/2026 (Source: [rittal.com/uk-en](http://rittal.com/uk-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4050.456 - Crimping machine RC

Electropneumatic crimping machine with 5-way magazine for processing insulated wire end ferrules in various cross-sections on a reel.



## Features

|                           |   |
|---------------------------|---|
| Model No.                 | AS 4050.456   |
| Design                    | Touchscreen display<br>Select the wire cross-section via touchscreen<br>Support may be fitted with a maximum of 23,000 wire end ferrules  |
| Product description       |   |
| Benefits                  | Easy to operate<br>Secure, fast processing of insulated wire end ferrules<br>No set-up time, thanks to automatic tool change<br>Simple, quick component mounting<br>No changing of the wire end ferrules required due to 5-way magazine |
| Technical specifications  | Cross-sections ranging from 0.5–2.5 mm <sup>2</sup> (AWG 20-14)<br>Crimping length 8 and 10 mm<br>Insertion length 27 mm (1.06 in.)   |
| Note                      | The standard crimping form is trapezoid – others available on request   |
| Dimensions                | Width: 335 mm<br>Height: 565 mm<br>Depth: 485 mm  |
| Compressed air connection | 5.5 bar   |
| Rated operating voltage   | 100 V - 240 V, 1~, 50 Hz/60 Hz  |

# Features

|                       |  |
|-----------------------|--|
| Apparent power        | 16 VA  |
| Compression           | Trapezoid crimp  |
| Cycle time            | 2 s  |
| Packs of              | 1 pc(s).   |
| Net weight            | 24.8 kg  |
| Gross weight          | 25.4 kg  |
| Customs tariff number | 84624900   |
| ETIM 9                | EC002778   |
| ETIM 8                | EC002778   |
| ECLASS 8.0            | 17130101   |
| Product description   | RC crimping machine, insulation stripping and crimping, for processing 5 wire end ferrules |