Rittal – The System.

Faster – better – everywhere.





AS 4051.130 Wire Station WS 540

State: 8/12/2025 (Source: rittal.com/uk-en)



AS 4051.130 - Wire Station WS 540

Mobile wiring workstation, height-adjustable, for flexible use in the workshop. For ergonomic, fatigue-free wire processing work.

Features

Model No.	AS 4051.130
Design	Basic edition
Product description	Mobile wiring workstation, height-adjustable, for flexible use in the workshop. For ergonomic, fatigue-free wire processing work.
Benefits	Electronically adjustable desk for the optimum working height, adjustable from 710 – 1250 mm Multiplex worktop, washable and scratch-resistant Ideal solution in conjunction with the length-cutting and crimping machines plus pre-assembled wires with the Wire Terminal Integral scale for quick manual measurements Prepared to accommodate a monitor for wire processing with Eplan Smart Wiring Optionally expandable with shelves for wire boxes, wire reels and holders for tools and small parts For flexible use in the workshop thanks to rubberised wheels Drawer with shadow board prepared for tools

© Rittal 2025

Features

Supply includes	Wiring table with electrical height adjuster		
	Connection cable, 7 m		
	7-way socket strip, with rocker switch		
	1 Wire Station WS 540		
	2 shelves		
	1 LED work light		
	2 mounting struts, vertical		
	1 storage box holder		
	2 adaptor brackets		
	1 universal support shelf 1 socket strip, 5-way 1 waste bin 4 wire pack holders, left 4 wire pack holders, right 1 wire coil holder, left		
		1 wire coil holder, right	
		Assembly instruction	The vertical mounting struts, Model No. 4051.106, are required for
			accessories such as storage box holders, magazine supports etc.
		Input voltage	230 V AC, 50 Hz
		Working height	Working height (min.): 710 mm
	Working height (max.): 1,205 mm		
Height adjustable y/n	Yes		
Applications	For manual wire processing		
Packs of	1 pc(s).		
Net weight	157		
Gross weight	218.3		
Customs tariff number	94032080		
EAN	4028177963665		
ETIM 8	EC002778		
ECLASS 8.0	21100208		

© Rittal 2025 3

Approvals

Explanations

Declaration of conformity

© Rittal 2025