# Rittal – The System.

Faster – better – everywhere.





# SE 5830.600 VX SE free-standing enclosure system

State: 4/11/2025 (Source: rittal.com/uk-en)



# SE 5830.600 - VX SE free-standing enclosure system

Free-standing sheet steel enclosure with stable enclosure body, two integral mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. System-compatible for configuration with VX25 accessories. Efficiency is enhanced, as the side panels no longer need to be fitted and large enclosure widths replace small bayed suites.







#### **Features**

Model No.	SE 5830.600
Material	Enclosure: Sheet steel 1.5 mm
	Door: Sheet steel, 2.0 mm
	Rear panel: Sheet steel, 1.5 mm
	Gland plates: Sheet steel, 1.5 mm
	Mounting plate: Sheet steel, 3.0 mm
Surface finish	Enclosure, door and rear panel: dipcoat-primed, powder-coated on
	the outside, textured paint
	Mounting plate and gland plates: Zinc-plated
Colour	RAL 7035

© Rittal 2025 2

# **Features**

Enclosure, solid top and sides Door(s) R/h door hinge with single-door enclosures, may be swapped to opposite side Mounting plate Gland plates Rear panel, detachable Lock: 3 mm double-bit 2 punched rails 18 x 39 mm Rear panel, one-piece  Dimensions Width: 600 mm Height: 1,800 mm Depth: 400 mm  Dimensions mounting plate (W x 499 mm x 1,696 mm H)  Protection category to IEC 60 529 IP 55  Protection category NEMA NEMA 12  Type rating to UL 50E Type 1 Type 2 Type 3 Type 3R Type 3R Type 12  IK Code IK10  Number of doors 1  Basic material Sheet steel Packs of 1 pc(s).  Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) Note on PCF category Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN 4028177959156  E-Number Sweden E3465407		
Height: 1,800 mm Depth: 400 mm  Dimensions mounting plate (W x H)  Protection category to IEC 60 529 IP 55  Protection category NEMA NEMA 12  Type rating to UL 50E Type 1 Type 2 Type 3 Type 3 Type 12  IK Code IK10  Number of doors 1  Basic material Sheet steel  Packs of 1 pc(s).  Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) 371.1 kg CO2 eq (Cat B)  Note on PCF category Category advanced by the self-declared  EAN 4028177959156	Supply includes	Door(s) R/h door hinge with single-door enclosures, may be swapped to opposite side Mounting plate Gland plates Rear panel, detachable Lock: 3 mm double-bit 2 punched rails 18 x 39 mm
H)  Protection category to IEC 60 529 IP 55  Protection category NEMA NEMA 12  Type rating to UL 50E Type 1 Type 2 Type 3 Type 3R Type 12  IK Code IK10  Number of doors 1  Basic material Sheet steel  Packs of 1 pc(s).  Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) 371.1 kg CO2 eq (Cat B)  Note on PCF category Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN 4028177959156	Dimensions	Height: 1,800 mm
Protection category NEMA  NEMA 12  Type rating to UL 50E  Type 1 Type 2 Type 3 Type 3R Type 12  IK Code  IK10  Number of doors  1  Basic material  Sheet steel  Packs of  1 pc(s).  Net weight  96.39  Gross weight  97.4  PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156		499 mm x 1,696 mm
Type rating to UL 50E  Type 1 Type 2 Type 3 Type 3R Type 12  IK Code  IK10  Number of doors  1  Basic material  Sheet steel  Packs of  1 pc(s).  Net weight  96.39  Gross weight  97.4  PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	Protection category to IEC 60 529	IP 55
Type 2 Type 3 Type 3R Type 12  IK Code IK10  Number of doors 1  Basic material Sheet steel  Packs of 1 pc(s).  Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) 371.1 kg CO2 eq (Cat B)  Note on PCF category Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN 4028177959156	Protection category NEMA	NEMA 12
Number of doors  Basic material  Packs of  1 pc(s).  Net weight  96.39  Gross weight  97.4  PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	Type rating to UL 50E	Type 2 Type 3 Type 3R
Basic material  Packs of  1 pc(s).  Net weight  96.39  Gross weight  97.4  PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	IK Code	IK10
Packs of 1 pc(s).  Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) 371.1 kg CO2 eq (Cat B)  Note on PCF category Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN 4028177959156	Number of doors	1
Net weight 96.39  Gross weight 97.4  PCF per pack (cradle-to-gate) 371.1 kg CO2 eq (Cat B)  Note on PCF category Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN 4028177959156	Basic material	Sheet steel
Gross weight  PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	Packs of	1 pc(s).
PCF per pack (cradle-to-gate)  Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	Net weight	96.39
Note on PCF category  Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared  EAN  4028177959156	Gross weight	97.4
approximately calculated and self-declared  EAN 4028177959156	PCF per pack (cradle-to-gate)	371.1 kg CO2 eq (Cat B)
	Note on PCF category	
E-Number Sweden E3465407	EAN	4028177959156
	E-Number Sweden	E3465407

© Rittal 2025 3

#### **Features**

ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

### **Approvals**

Approvals	UL + C-UL (listed)
Certificates	Surface finish Protection category
Explanations	Declaration of conformity  Declaration of conformity UK  PCF-declaration

#### Tender text

Enclosure (System Enclosure VX SE, sheet steel)

Control cabinet for individual installation in integral construction, consisting of basic body, door, rear wall and base assembly. Basic body made of profiled side walls and roof. Housing profile with System perforation in 25 mm DIN dimensional grid. Vertical profiles, as well as front and rear roof frame profile with two mounting levels for space-saving system expansion. Rear panel screwed, base assembly welded in, consisting of base frame and multiple divided gland plates, door hinged on the right.

#### Door:

with horizontal double foamed PU seal, with removable tubular doorframe with perforation in DIN dimension grid of 25 mm, quadruple locked, double-bit insert according to DIN 43668, Hinges right hinged, exchangeable, with

© Rittal 2025

captive hinge pins, door opening angle 130° according to VDI, retrofittable to 180°, automatic potential equalisation to the housing body. Gland plates:

3-part, removable and exchangeable, mounted, automatic potential equalisation to the housing body.

Rear panel:

with foamed PU seal, screwed, automatic potential equalisation to the housing body. Mounting plate:

C-edged at the sides, via integrated plastic gliders and mounting rails, depth adjustable in grid of 25 mm. Including mounting grid for simplification the positioning of components.

Material:

Body, rear panel, top, bottom panels: 1.5 mm sheet steel

door: 2 mm sheet steel

mounting plate: 3 mm sheet steel

Surface finish:

Triple surface treatment for corrosion protection and resistance to mineral oils, lubricants, processing emulsions and solvents, nanoceramics coating, electrophoresis dip primer, outer surfaces powder coated in RAL 7035 texture. mounting plate and gland plates: galvanised

Protection class:

IP 55 according to IEC 60 529 protection class to UL 508A: Type 12, 3R Impact protection to IEC 62 262: IK10

Dimension (W x H x D): 600x1800x400 mm

© Rittal 2025 5