

Faster – better – everywhere.





CP 6372.563 Comfort Panel

State: 29/08/2025 (Source: rittal.com/uk-en)



CLIMATE CONTROL


IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

CP 6372.563 - Comfort Panel

Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability. Protection category IP 65 to IEC 60 529.



Features

Model No.	CP 6372.563
Design	Support arm connection Ø 130 mm
Benefits	Aluminium enclosure, high thermal conductivity for optimum
	passive heat dissipation.
	Low weight coupled with high stability
	Compatible with all Rittal stand and support arm systems
Material	Enclosure: Extruded aluminium section
	Corner pieces: Die-cast zinc
	Corner protectors: Plastic
General colour	Natural anodised
Colour	Enclosure: Natural anodised
	Corner pieces: RAL 7035
	Corner protectors: similar to RAL 7024
Supply includes	Enclosure with cut-out for support arm connection
	3 mm double-bit lock insert may be exchanged for 41 mm lock
	inserts, plastic handles and T handles, type C
	Seals and assembly parts for front panels
	Screw-fastened rear panel, enclosure hinged at the front with side double-bit lock insert

Features

Dimensions	Width: 628.5 mm
	Height: 708.5 mm
	Depth: 209 mm
Installation depth	191 mm
IP protection category to IEC 60 529	IP 65
Protection category NEMA	NEMA 12
To fit front panel width	520 mm
To fit front panel height	600 mm
Design	Servicing access from the rear
Note	The support arm connection may be swapped over by rotating the enclosure
Basic material	Aluminium
Lock	Lock version: Crescent-shaped cam
	Number of locks: 2
	Lock insert: 3 mm double-bit
Packs of	1 pc(s).
Net weight	18.7
Gross weight	20.34
EAN	4028177663145
ETIM 9	EC002504
ECLASS 8.0	27180505

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK