

Faster – better – everywhere.





VX 7993.128 Bayed enclosure system VX25

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 11/07/2025 (Source: rittal.com/uk-en)

POWER DISTRIBUTION >> CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

VX 7993.128 - Bayed enclosure system VX25 BMW AG Group standard

Valid in all BMW AG component and car factories. VX25 enclosures with 200 mm high base/ plinth, for TMO.

Features

Model No.	VX 7993.128
Product description	Valid in all BMW AG component and car factories. VX25 enclosures with 200 mm high base/plinth, for TMO.
Material	Enclosure frame: Sheet steel, 1.5 mm
	Roof: Sheet steel, 1.5 mm
	Door: Sheet steel, 2.0 mm
	Rear panel: Sheet steel, 1.5 mm
	Gland plates: Sheet steel, 1.5 mm
	Mounting plate: Sheet steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and gland plates: Zinc-plated
Colour	RAL 7035
Supply includes	Door(s) with fitted 180° hinges 8618.330
	Door(s) with fitted comfort handle for profile half-cylinders
	8618.250 including fitted adaptor kit for double-bit lock insert 7993.200
	Base/plinth height: 200 mm, consisting of corner pieces and base/
	plinth components front and rear 8660.02X, height of base/plinth
	trim panels 2 x 100 mm at the front and 1 x 200 mm at the rear
	With zinc-plated mounting plate, mounted in the rearmost position
	in the final raster hole
	With LED system light 2500.220, 24 V at the front, with infeed
	2500.410 and with fitted door-operated switch 2500.460
Dimensions	Width: 800 mm
Dimensions	Width: 800 mm Height: 2,000 mm

Features

Height including base/plinth	2,200 mm
Dimensions mounting plate (W x H)	699 mm x 1,896 mm
Number of doors	1
Packs of	1 pc(s).
Net weight	131.6
Gross weight	143