Rittal – The System.

Faster – better – everywhere.



# SV 9677.300

# NH slimline fuse-switch disconnector

State: 25/11/2026 (Source: www.rittal.com/uk-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# SV 9677.300 - NH slimline fuse-switch disconnector

3-pole, for bar systems with 185 mm centre-to-centre spacing.

## Features

| | |
|---|---|
| Model No. | SV 9677.300 |
| Design | 3-pole, switchable |
| Material | Polyamide<br>Fire protection corresponding to UL 94-V0<br>Contact tracks: Partially silver-plated hard copper |
| Colour | Chassis: RAL 7035<br>Cover: RAL 7001<br>Handle: RAL 7016 |
| For NH size | 3 |
| For bar systems with centre-to-centre spacing | 185 mm |
| Cable outlet | Top/bottom |
| Type of electrical connection | Bolt M12 |
| Number of poles | 3-pole |
| Rated operating voltage | 800 V (AC), 3~ |
| Rated operating current max. | 630 A |
| Note | When using components on busbars with contact hazard protection cover, the contact terminal must be used |
| Test specification | IEC/DIN EN 60 947-3<br>DIN EN 60 269-2 (fuse inserts) |
| For converter installation | Yes |
| Dimensions | Width: 100 mm<br>Height: 670 mm |
| Connection of round conductors | 6 - 240 mm² |
| To fit busbars | Height: 10 mm |

© Rittal 2026

# Features

| | |
|---|---|
| Packs of | 1 pc(s). |
| Net weight | 5.7 kg |
| Gross weight | 5.86 kg |
| Copper weight (kg per piece) | 2.47 |
| Customs tariff number | 85365080 |
| ETIM 9 | EC001046 |
| ECLASS 8.0 | 27371402 |
| Product description | SV NH slimline fuse-switch disconnector, size 3, 630 A, 800 V, 3-pole, bolt M12, 185 mm, for current transformer installation |

# Approvals

| | |
|---|---|
| Approvals | CQC-CCC |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |