## Rittal - The System.

Faster – better – everywhere.





# AX 2261.540 AX wall-mounted housing, 3-part


State: 8/26/2025 (Source: rittal.com/us-en)



## AX 2261.540 - AX wall-mounted housing, 3-part

The delivery concept of the three-part AX wall-mounted enclosure reduces complexity and increases flexibility. Thanks to the AX/VX modular system, the enclosures are suitable for various applications. The three-part structure ensures easy access.







#### **Features**

Model No.	AX 2261.540
Version	Wall-mounted housing IT
Material	Wall and hinged part: Carbon steel, 1.5 mm
	Viewing window: Single-pane safety glass, 3 mm
Surface finish	Powder-coated
Color	Wall and hinged part: RAL 7035
	Viewing door: RAL 7035/7015 (slate gray)
Supply includes	Wall section: Flange (gland) plate, solid, top and bottom
	Hinged part with 25 mm pitch pattern in the front and rear frame,
	two 19" profile angles at the front, fixed in place
	Designer viewing door
	Center part lock: 3 mm double bit
	Lock design – glazed door: Security lock 3524 E
	Mini-comfort handle
Height units	15 U

© Rittal 2025 2

## Features

Dimensions	Width: 600 mm
	Height: 746 mm
	Depth: 473 mm
	Width: 23.6 "
	Height: 29.4 "
	Depth: 18.6 "
No. of locks	1
Load capacity of hinged part (static)	750 N
Load capacity of wall section (static)	250 N
Base material	Carbon steel
Lock	Lock version: Mini-comfort handle
	Lock Insert: Security lock insert no. 3524 E
Protection category IP to EN 60 529	IP 54 in conjunction with solid gland plate top and bottom
Packaging unit	1 pc(s).
Net weight	40.75
Gross weight	43
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	94032080
EAN	4028177983359
ETIM 9	EC002500
ETIM 8	EC002500
ECLASS 8.0	27180101

## Approvals

|--|

© Rittal 2025 3